



البرج العالي لصناعة (ش.ذ.م.م.)
HIGH TOWER INDUSTRIES L.L.C.

HIGH TOWER INDUSTRIES
hitekTM
QUALITY PAINT SYSTEMS

P.V.A PRIMER

P.V.A PRIMER

It is water based PVA Co-polymer for priming of plaster, concrete and brickwork. It is Alkali & Fungus resistant. **hitek**TM PVA Primers are used internally on a variety of surfaces and possess strong bond properties with the substrate.

'P.V.A PRIMER' Technical Data

Specific Gravity	1.35 ± 0.5
Area Coverage	8-10 m ² /litre [Approx.] - Depending on the surface
Viscosity	15-20 Poises
Flash Point	Non-Flammable
No. of Coats	1-2
Recoatibility	After 2 hours
Finish	Matt
Drying	30 Minutes
Colour	White
Packing	5 US Gallon Drum 1 US Gallon Drum
Storage/Shelf life	6 months from the DOM under dry condition

Application Advisable

Priming Coat	hitek TM PVA Primer
Intermediate Coat	hitek TM Stucco Filler
Coating Layer	hitek TM Emulsion

Surface Preparation

Clean the surface thoroughly with a stiff bristle brush to remove loose adherent dust etc. Make sure that the substrate is clean to allow for maximum adhesion and bonding.

Application

Brush, Roller, or Spray

USE

Can be used for Interior & Exterior surfaces, apply directly on plaster, concrete, masonry surfaces etc. **hitek**TM PVA Primer can be applied directly on concrete, cement and other masonry surfaces. **hitek**TM PVA Primer is a multifaceted and universally applied product that promotes quality and efficiency in its application.

Tel. : +971 4 342 6106
Fax : +971 4 354 8803

admin@reliantgroup-uae.com
www.reliantgroup-uae.com



إكسبو 2020
دبي، الإمارات العربية المتحدة
DUBAI, UNITED ARAB EMIRATES

We are Reliant . Established in 1981

Office M-01
The Business Centre
P.O Box 60859, Dubai
United Arab Emirates