



البرج العالي لصناعة (ش.ذ.م.م.)  
HIGH TOWER INDUSTRIES L.L.C.

HIGH TOWER INDUSTRIES  
**hitek**<sup>TM</sup>  
QUALITY PAINT SYSTEMS

INTERIOR EMULSION PAINT

## INTERIOR EMULSION PAINT

**hitek**<sup>TM</sup> Interior Emulsions are a breed of economical water-borne thixotropic interior decorative wall paints based on vinyl co-polymer emulsion(s). Available in a variety of colours, this line of decorative paints are primarily produced and sold in standard white as well as off white (10B15).

### 'INTERIOR EMULSION' Technical Data

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| Specific Gravity   | 1.46 ± 0.5                                                      |
| Area Coverage      | 7-10 m <sup>2</sup> /litre [Approx.] - Depending on the surface |
| Viscosity          | Thixotropic                                                     |
| Flash Point        | Non-Flammable: nil                                              |
| No. of Coats       | 2-3                                                             |
| Recoatibility      | After 3 hrs in between each layer                               |
| Finish             | Matt                                                            |
| Drying             | Surface Dry 15-20 Minutes                                       |
| Packing            | 5 US Gallon Drum<br>1 US Gallon Drum                            |
| Storage/Shelf life | 6 months from the DOM under dry condition                       |
| Colour             | White / Off White (10B15)                                       |

### Application Advisable

|                   |                                              |
|-------------------|----------------------------------------------|
| Priming Coat      | <b>hitek</b> <sup>TM</sup> P.V.A. Primer     |
| Intermediate Coat | <b>hitek</b> <sup>TM</sup> Stucco Filler     |
| Coating Layer     | <b>hitek</b> <sup>TM</sup> Interior Emulsion |

### Surface Preparation

The surface must be dry and properly cleaned. This applies to concrete and other cement or plaster surface(s). All dust and loose flaking material must be removed. Make sure that the surface is clean to allow for maximum adhesion and bonding.

### Application

Brush, Roller, or Spray

### USE

The product can be applied on any masonry, board and wooden surface(s). **hitek**<sup>TM</sup> Interior Emulsions are a multifaceted and universally applied product that promotes quality and efficiency in its application.

Tel. : +971 4 342 6106  
Fax : +971 4 354 8803

admin@reliantgroup-uae.com  
www.reliantgroup-uae.com



إكسبو 2020  
دبي، الإمارات العربية المتحدة  
DUBAI, UNITED ARAB EMIRATES

We are Reliant . Established in 1981

Office M-01  
The Business Centre  
P.O Box 60859, Dubai  
United Arab Emirates