

FENOCOAT MATT

hitek FENOCOAT MATT is your solution for internal quality acrylic copolymer based paint with excellent workability and color retention properties. Ideal as an internal decorative finish, **hitek** FENOCOAT MATT is alluring as a flat and durable material as well as in its composition of antibacterial elements that make for a safe and secure environment.


As manufacturers of the **hitek** brand, our **hitek** FENOCOAT MATT paint is guaranteed in quality as its field properties make it an efficient product in its installation and durability. **hitek** FENOCOAT MATT is created using a perfect blend of high quality raw materials creating an optimal bonding environment atop other layers of **hitek** foundation materials. Advantages include: (a) that it is supplied and guaranteed directly by the manufacturer; (b) that it is easy to apply; (c) that it has excellent workability onsite; (d) that its antibacterial, washable and non-toxic properties make it an ideal and safe solution for internal decorative purposes.

'FENOCOAT' TECHNICAL DATA

Composition	Contains weather resistant pigmentation, binders and antibacterial agents.
Color & Finish	White / Off-White - MATT
Specific Gravity	1.3 ± 0.5
Flash Point	Zero
Consistency	Thixotropic
No. of Coats / Recoatability	2-3 Coats
Surface Drying Time	15-20 mins with application interval of 4 hours
Area Coverage	6-7 m ² per liter – surface dependent
Shelf Life / Storage	6 months from the DOM – no direct sunlight
Packing	5 US Gallon Drum / 1 US Gallon Drum

APPLICATION ADVISABLE

Priming Coat	hitek PVA Primer
Intermediate Coat	hitek Stucco Filler
Final Coating	hitek Fenocoat Matt



FENOCOAT MATT

SYSTEM OF APPLICATION

Preparation:

The surface should be clean and dry. On new surfaces, brush off any dust and loose particles such as adherent concrete. On surfaces preexisting / previously painted, remove chipped flakes, algae and other contaminants in order to optimize bonding.

Drying Time:

General associated with air circulation, internal temperatures, film thickness and the number of coats having been applied.

Application:

hitek FENOCOAT can be applied either manually or mechanically. Application methodology can range from brush and roller applications to even spray applications depending on the effect required of the material as per the satisfaction of the end-user.

Usage:

The material will adhere to surfaces such as concrete, plasters, asbestos and boards. Internal applications recommended. Should an external application be required, please ensure that the area(s) are not directly exposed to the elements. The manufacturer will not be held responsible for any claim arising out of non-performance of the product due to incorrect application procedures or usage of product for non-recommended purposes.

Health & Safety:

hitek FENOCOAT must be handled with care to prolong its shelf life. Stir the material well prior to usage and ensure adequate preparation prior to application as well as the appropriate drying time during intermediate coating installation. Store in a cool, dry place away from direct heat and sun light.

hitek materials have no specific health hazards. It is non-toxic, non-flammable and contains strong antibacterial properties. Do not heavily breathe/inhale the product and avoid direct contact with eyes and skin. Wash with plenty of clean water and seek medical help if required. Use protective kits such as masks, gloves and spectacles as an additional precaution.

