



البرج العالي لصناعة (ش.ذ.م.م.)
HIGH TOWER INDUSTRIES L.L.C.

HIGH TOWER INDUSTRIES
hitekTM
QUALITY PAINT SYSTEMS

TEX PRIMER

TEX PRIMER

hitekTM Tex Primer is used prior to the application of all textured coatings. Its composition is based on modified acrylic emulsions and has qualities of excellent adhesion to substrates such as cement, concrete, plywood and so forth.

'TEX PRIMER' Technical Data

| | |
|--------------------|--|
| Specific Gravity | 1.6 ± 0.5 |
| Area Coverage | 12-14 m ² /litre [Approx.] - Depending on the surface |
| Viscosity | 105 ± 5 K.U |
| Flash Point | Non-Flammable - nil |
| No. of Coats | 1 |
| Recoatibility | 2 nd Coat if required |
| Finish | Matt |
| Drying | Surface Dry 1-1.5 hour, Hard Dry 6-8 hours |
| Colour | White |
| Packing | 5 US Gallon Drum 1 US Gallon Drum |
| Storage/Shelf life | 6 months from the DOM under dry condition |

Application Advisable

| | |
|-------------------|--|
| Priming Coat | hitek TM Tex Primer |
| Intermediate Coat | hitek TM Multifinish |

Surface Preparation

Clean the surface thoroughly with a stiff bristle brush to remove loose adherent dust etc. Make sure that the substrate is clean to allow for maximum adhesion and bonding.

Application

Brush, Roller, or Spray

USE

hitekTM Tex Primer can be applied directly on concrete, cement, brickwork, wood and so forth. **hitek**TM Tex Primer is a multifaceted and universally applied product that promotes quality and efficiency in its application.

Tel. : +971 4 342 6106
Fax : +971 4 354 8803

admin@reliantgroup-uae.com
www.reliantgroup-uae.com



إكسبو 2020
دبي، الإمارات العربية المتحدة
DUBAI, UNITED ARAB EMIRATES

We are Reliant . Established in 1981

Office M-01
The Business Centre
P.O Box 60859, Dubai
United Arab Emirates