



MULTIFINISH

An acrylic based coating used for both External as well as interior decorative finishes. The product contains high water resistant properties and can be applied in forms that are textured, decorative and protective when applied on concrete, blocks, bricks and so forth. **hitek**TM Multifinish can be applied to small, medium or largely specified textured finishes.

'MULTIFINISH' Technical Data

Specific Gravity	1.7 ± 0.5
Area Coverage	2-3 m ² /litre [Approx.] - Depending on the surface thickness & method of application
Viscosity	Paste
Flash Point	Non-Flammable: nil
Drying	Surface Dry after 1 hour, Hard Dry after 8 hours
Finish	Texture [Satin Effect]
Storage/Shelf life	6 months from the DOM under dry condition
Colour	White
Packing	5 US Gallon Drum 1 US Gallon Drum

Application Advisable

Priming Coat	hitek TM Tex Primer
Intermediate Coat	hitek TM Multifinish
Coating Layer	hitek TM Acrylic Topcoat

Surface Preparation

Remove dust, loose or flaking material. Grind off all protrusions and filling cavities with a cement based filler. Make sure that the surface is clean to allow for maximum adhesion and bonding.

Application

Brush, Roller, Spray, Steel Edged Tool(s) etc

USE

For exterior and interior surface(s), apply **hitek**TM MULTIFINISH Texture as an intermediate coat by spray gun before applying **hitek**TM Acrylic Top Coat. It also helps to correct and mask the undulations on the surface. **hitek**TM Multifinish is a multifaceted and universally applied product that promotes quality and efficiency in its application.

