

البرج العالي لصناعة HIGH TOWER INDUSTRIES



TILE GROUT

Grout is a blend of specially selected cements, fillers, synthetic organic polymers, metal oxides and chemical improving agents. When added to water it readily blends to produce a smooth creamy paste which when set, is water and mould resistant.

It is a smooth and creamy material that has non-shrinkage properties that work at 90 minutes at 20°C and at 30 minutes at 35°C respectively.

Uses

hitck Tile Grout is a premixed cement based, non shrink water proof grout for filling of tile joints in kitchens, bathrooms and indeed all tiled apartments/homes and so forth. **hitck** tile grouting applications include both horizontal and vertical installations.

Applications

Add water to produce a general purpose grout for walls and floors. **hitek** Tile Grout can be used with all types of tiles, glass blocks, ceramic tiles, slate and stone. Place tile joint filler correctly between the tiles with a rubber spatula, ensuring that it is completely locked in between the joints. Grouting can take place after 24 hours. **hitek** Tile Grout can be applied with a rubber or plastic spatula or similar to obtain complete, regular and compact filling of the joints. Grouting should not start before the tile adhesive has dried completely. Mix thoroughly with clean water in a clean and dry porcelain dish to ensure uniformity of colour.

Packing

Available in 10kg bags that can be stored for 6 months if kept in dry condition(s).

Additional Information

Our tile grouts and glues are packaged into **hitek** Tile Installation Systems. With **hitek** Tile Grouts, it's not only "good looks" that matter, it is substance as well. Grouts not only need to look perfect, they also need to be robust, durable and suitable for your specific needs. **hitek** Tile Grout is available in white or grey.



